

Claw Hammer Indestructible Handle

CLID

Also known as a Nailing Hammer these are used in woodworking, prying & finishing jobs

BS 876
For material, hardness & performance

Handle

2 spring steel bars are locked with the hammer head using steel locking plates ensuring that the head never gets dislodged

Ergonomic rubber grip handle absorbs shock & vibration reducing fatigue

Head

Hammer Head is forged from special steel & induction case hardened 50-58 HRC for extended life

Special bonding process ensures that the handle and head never get loose. Well shaped, curved claw is tapered for maximum grip & higher leverage when gripping a nail

UTILITY

- Pulling Out Nails
- Lifting Floorboards
- Carpentry Work



Steel Locking Plate



2 Spring Steel Bars



Ergonomic Rubber Grip Handle

ORDERING INFORMATION

CAT NR.	ORD NR.	HEAD WEIGHT (GMS)	HEAD WEIGHT (OZ)	OVERALL LENGTH (INCH)	OVERALL LENGTH (MM)	BOX QTY.
CLID/16/13	34535	450	16	13	330	12

WARNING

Do not strike objects harder than 46 HRC. Striking items of a greater hardness is liable to cause fracture or chipping. Do not use a claw hammer for striking cold chisels or for pulling out masonry nails