

**17**

## Drilling Hammers Fibreglass Handle

**DHFG**

For day-to-day demands of professional users

**Head**

Fully forged head is induction hardened 50-58 HRC and tempered for maximum strength and durability

Duly machined and polished faces are beveled to prevent chipping

**Handle**

Lightweight yet durable dual injection moulded fibreglass handle for controlled and balanced swing

Designed with a 25% wider neck, handles are covered with a polypropylene jacket for protection against overstrikes

TPR grip on handle absorbs shock and vibration and provides a non-slip grip

Handles securely attached to the hammer head using a tough epoxy adhesive ensuring that the head does not fly away even with rough use


**B107.400- 2018**
**BS 876**

For material, hardness &amp; performance

**UTILITY**

- Striking cold chisels, concrete chisels & brick bolsters
- Drive in stakes
- Rebar into the ground
- Break through concrete floors


**ORDERING INFORMATION**

CAT NR.	ORD NR.	HEAD SIZE		OVERALL LENGTH		BOX QTY.
		(LBS)	(GMS)	(INCH)	(MM)	
DHFG/2/11	36560	2	900	11	280	8
DHFG/3/11	36561	3	1300	11	280	8

**WARNING**

Do not strike objects harder than 46 HRC. Striking items of a greater hardness is liable to cause fracture or chipping