

## Quick Woodworking Clamps

KBC

PCB

Manufactured from "K" section steel profiled to minimize flexing & bending

Quickest adjustment mechanism - simply lifting the aluminium die-cast handle allows the sliding jaw to be moved anywhere on the rail

Four hardened rollers in the moving head maintain a constant 90° angle under load

Clamp jaws are encased in non-marring, glue resistant polypropylene casing

### Throat Depth (T)

3-11/32" (85 mm)

### Width of clamp face (W)

1-7/16" (37 mm)

### Section

1-1/8" x 3/8" x 1/4" (29 x 9 x 6 mm)



The clamp is fitted with a plastic end stop to maintain it at level. By removing this end stop, the movable jaw can be reversed and be used as a spreader - very useful in building window & door frames



### PCB/4/ST

Set of 4 Parallel Blocks.  
These are useful for efficient & accurate set up of raised panels, window & door frames, boxes etc.

### ORDERING INFORMATION

CAT NR.	ORD NR.	CLAMPING CAPACITY		BOX QTY.
		(INCH)	(MM)	
KBC/12	39180	12	300	10
* KBC/24	39181	24	600	10
KBC/31	39182	31	775	5
* KBC/40	39183	40	1000	5
KBC/50	39184	50	1250	5
SET OF 4 PARALLEL CLAMP BLOCKS				
PCB/4/ST	39190			10

\* Best Seller

