

## Grease Pump Kit

**TMK-GP2**


Trolley mounted kits are ideal for use in workshops, garages, shop floors providing complete portability for everyday lubrication needs

**KIT INCLUDES**

<b>A</b>	50:1 Air Operated Grease Pump
<b>B</b>	<b>Grease Control Valve</b> Fitted with 360° Z swivel for trouble free dispensing
<b>C</b>	<b>Connecting Hose</b> 84" x 1/4" I.D. (2m x 6.5 mm I.D.) - SAE R2
<b>D</b>	<b>Steel Drum Cover</b> 15" (381 mm) Prevents impurities from contaminating grease and keeps pump in vertical position
<b>E</b>	<b>Rubber Lined Follower Plate</b> O.D. Steel End: 12-11/16" (322 mm) O.D. Plate: 15" (380 mm) I.D. Grommet: 1-3/16" (29.5 mm)
<b>F</b>	<b>Drum Trolley - Heavy Duty</b> Manufactured from 4 mm thick steel sheet in powder coated finish Front Wheels: 6" (150 mm) polyurethane with nylon rim Rear castors with toe lock
<b>G</b>	<b>*Filter-Regulator Combination &amp; Lubricator with Pressure Gauge (FRCLM)</b> Port Size: 1/4" Type: Miniature Filter: 40 micron

\*On selected models


**WETTED COMPONENTS**

Steel, Brass, Aluminium, Polyurethane & Nitrile  
Rubber

**RECOMMENDED USE**

With light and self collapsing grease up to  
NLGI No. 2

**ORDERING INFORMATION**

CAT NR.	ORD NR.	DESCRIPTION	THREADS	BOX QTY.
TMK/GP2/A/BSP	45821	Pump kit with FRCLM unit	1/8" BSPT	1
TMK/GP2/A/N	45826	Pump kit with FRCLM unit	1/8" NPT	1
TMK/GP2/B/BSP	48910	Pump kit without FRCLM unit	1/8" BSPT	1
TMK/GP2/B/N	48911	Pump kit without FRCLM unit	1/8" NPT	1

**SPECIFICATIONS**

WORKING PRESSURE	30-150 PSI	2-10 BAR
MAX. AIR PRESSURE	150 PSI	10 BAR
MAX. OUTLET PRESSURE	7,500 PSI	500 BAR
AIR INLET CONNECTION	1/4" (F)	
PUMP OUTLET	1/4" (F)	
AIR CONSUMPTION	72 GPM	270 LPM
NOISE LEVEL	85 db	
GREASE OUTPUT (MAX.)	2.42 lbs./min.	1.1 kg/min.
FOR USE WITH	120 lbs. drums	50-60 kg drums