

Worklight

Glare Free

LED-398



Pocket sized, glare-free worklight

Integrated

- 3W SMD Top Torch
- 6W COB Main Light

User controlled output

	1ST PRESS	2ND PRESS	3RD PRESS
INTENSITY	TOP TORCH	MAIN LIGHT	
LUMEN	HIGH	LOW	HIGH
RUN TIME	250	150	600
	6 hrs	8 hrs	3 hrs

Strudy Construction

a. IP 65 Rated

Protected against dust and effects of water jets from any direction

b. IK 07 Rated

Impact Resistant ABS Body will withstand tough jobsite conditions

Glare Free light helps in working for longer times as there is no shadow formation

Fully Flexible

360° Swivelling Body and 210° swivelling base stand to direct light wherever needed

Hands Free Operation

Rotating bracket equipped with

Base Magnets: 2 super strong magnets to mount lights flat on any metallic surface

End Magnets: To mount the light vertically onto any metallic surface

Charging of Battery

Type C fast charging protected by rubberized bezel (cable included)



Hands free operation




Base magnets



End magnets

POWER SOURCE



3.7V 2600 mAh

ORDERING INFORMATION

CAT NR.	ORD NR.	SIZE (L×H×D)		BOX QTY.
		(INCH)	(MM)	
LED/398	55126	4-23/32×1-31/32×1-11/32	117×50×34	10